


### Produktgruppe K LH5B

Klemmhebel mit Gewindebolzen, verstellbar




#### Standardfarben

- schwarz

#### Material

- Grundkörper: glasfaserverstärktes Polyamid (PA-GF)
- Gewindebolzen: Stahl verzinkt
- Einstellschraube: Stahl verzinkt



| A   | B   | D  | D1 | H  | h  | h1 | h2 | M   | 10 | 15 | 20 | 25 | 30 | 40 | 50 | 60 |
|-----|-----|----|----|----|----|----|----|-----|----|----|----|----|----|----|----|----|
| mm  | mm  | mm | mm | mm | mm | mm | mm |     | mm | mm | mm | mm | mm | mm | mm | mm |
| 40  | 50  | 17 | 12 | 42 | 33 | 7  | 15 | M5  | x  |    | x  |    | x  |    |    |    |
| 40  | 50  | 17 | 12 | 42 | 33 | 7  | 15 | M6  |    | x  | x  | x  | x  |    |    |    |
| 60  | 70  | 22 | 15 | 42 | 37 | 8  | 14 | M6  |    | x  | x  | x  | x  | x  | x  |    |
| 60  | 70  | 22 | 15 | 42 | 37 | 8  | 14 | M8  |    | x  | x  |    | x  | x  | x  | x  |
| 60  | 70  | 22 | 15 | 42 | 37 | 8  | 14 | M10 |    |    |    |    |    | x  |    |    |
| 80  | 95  | 27 | 19 | 59 | 49 | 9  | 20 | M10 |    |    | x  |    | x  | x  | x  |    |
| 80  | 95  | 27 | 19 | 59 | 49 | 9  | 20 | M12 |    |    |    |    | x  | x  | x  |    |
| 100 | 117 | 38 | 25 | 85 | 60 | 12 | 20 | M12 |    |    |    |    | x  | x  | x  |    |
| 100 | 117 | 38 | 25 | 85 | 60 | 12 | 20 | M14 |    |    |    |    | x  | x  | x  |    |
| 100 | 117 | 38 | 25 | 85 | 60 | 12 | 20 | M16 |    |    |    |    | x  | x  | x  |    |

#### Bestellbeispiel

- Gruppe + A + M + Gewindelänge ---> K LH5B - 60 M6x 20