


Product Group RSAF

Angled glides for round tubes for furniture/framework with welded felt




Standard Colours

- black RAL 9005

Material

- Base body: Polyethylene (PE)
- Slide base: synthetic needle felt (polyester)



Product options on inquiry

- Special colours (colours, minimum quantities, set-up costs, pricing and surcharges)

Order Number	α °	D mm	H mm	H1 mm	L mm	t mm
RSAF 16x2-2,5 /6°/20	6	16	6,5	3,5	20	2-2,5
RSAF 16x2-2,5 /9°/20	9	16	6,8	3,5	20	2-2,5
RSAF 16x2-2,5 /12°/20	12	16	7,2	3,5	20	2-2,5
RSAF 16x2-2,5 /15°/20	15	16	7,9	3,5	20	2-2,5
RSAF 16x2-2,5 /18°/20	18	16	9,5	3,5	20	2-2,5
RSAF 16x2-2,5 /24°/20	24	16	10,4	3,5	20	2-2,5
RSAF 18x1,5-2 /6°/20	6	18	6,5	3,5	20	1,5-2
RSAF 18x1,5-2 /9°/20	9	18	6,7	3,5	20	1,5-2
RSAF 18x1,5-2 /12°/20	12	18	7,2	3,5	20	1,5-2
RSAF 18x1,5-2 /15°/20	15	18	9	3,5	20	1,5-2
RSAF 18x1,5-2 /18°/20	18	18	9,3	3,5	20	1,5-2
RSAF 18x1,5-2 /24°/20	24	18	11,4	3,5	20	1,5-2
RSAF 19x1,5-2 /6°/20	6	19	6,7	3,5	20	1,5-2
RSAF 19x1,5-2 /9°/20	9	19	7	3,5	20	1,5-2
RSAF 19x1,5-2 /12°/20	12	19	7,5	3,5	20	1,5-2
RSAF 19x1,5-2 /15°/20	15	19	9,2	3,5	20	1,5-2
RSAF 19x1,5-2 /21°/20	21	19	11	3,5	20	1,5-2
RSAF 19x1,5-2 /24°/20	24	19	11,5	3,5	20	1,5-2
RSAF 20x1,5-2 /9°/20	9	20	7	3,5	20	1,5-2
RSAF 20x1,5-2 /12°/20	12	20	9	3,5	20	1,5-2
RSAF 20x1,5-2 /15°/20	15	20	10	3,5	20	1,5-2
RSAF 20x1,5-2 /18°/20	18	20	11	3,5	20	1,5-2
RSAF 20x2-2,5 /9°/20	9	20	7	3,5	20	2-2,5
RSAF 20x2-2,5 /12°/20	12	20	9	3,5	20	2-2,5



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

Order Number	α °	D mm	H mm	H1 mm	L mm	t mm
RSAF 20x2-2,5 /15°/20	15	20	10	3,5	20	2-2,5
RSAF 20x2-2,5 /18°/20	18	20	11	3,5	20	2-2,5
RSAF 22x1,2-2 /9°/20	9	22	7,8	3,5	20	1,2-2
RSAF 22x1,2-2 /12°/20	12	22	8	3,5	20	1,2-2
RSAF 22x1,2-2 /15°/20	15	22	10	3,5	20	1,2-2
RSAF 22x1,2-2 /18°/20	18	22	10	3,5	20	1,2-2
RSAF 22x1,2-2 /21°/202	21	22	11,5	3,5	20	1,2-2
RSAF 22x1,2-2 /24°/20	24	22	12	3,5	20	1,2-2
RSAF 22x2-2,5 /9°/20	9	22	7,8	3,5	20	2-2,5
RSAF 25x1,5-2 /6°/20	6	25	7,2	3,5	20	1,5-2
RSAF 25x1,5-2 /9°/20	9	25	8,5	3,5	20	1,5-2
RSAF 25x1,5-2 /12°/20	12	25	9,5	3,5	20	1,5-2
RSAF 25x1,5-2 /15°/20	15	25	12	3,5	20	1,5-2
RSAF 25x1,5-2 /18°/20	18	25	12	3,5	20	1,5-2