


### Product Group MFMB

Machine feet made of stainless steel with rubber base and fixing strap




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The machine foot can be fixed to the floor.
- The cast-in mounting plate ensures that the foot dampens vibrations even after it has been fixed to the floor.
- The rounded and hygienic design of this type enables easy and quick cleaning.
- The embedded rubber meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 5°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D   | A  | B  | d     | F max. | H  | M   | WAF | 50 | 70 | 100 | 150 | 180 | 230 | 310 |
|-----|----|----|-------|--------|----|-----|-----|----|----|-----|-----|-----|-----|-----|
| mm  | mm | mm | mm    | kg     | mm |     | mm  | mm | mm | mm  | mm  | mm  | mm  | mm  |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M10 | 8   | x  | x  | x   | x   | x   | x   |     |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M12 | 10  | x  | x  | x   | x   | x   | x   |     |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M20 | 15  |    | x  | x   | x   | x   | x   | x   |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M24 | 19  |    | x  | x   | x   | x   | x   | x   |
| 75  | 67 | 52 | 14,85 | 800    | 22 | M30 | 24  |    | x  | x   | x   | x   | x   | x   |
| 100 | 82 | 67 | 14,85 | 1000   | 32 | M12 | 10  | x  | x  | x   | x   | x   | x   |     |
| 100 | 82 | 67 | 14,85 | 1000   | 32 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |
| 100 | 82 | 67 | 14,85 | 1000   | 32 | M20 | 15  |    | x  | x   | x   | x   | x   | x   |
| 100 | 82 | 67 | 14,85 | 1000   | 32 | M24 | 19  |    | x  | x   | x   | x   | x   | x   |
| 100 | 82 | 67 | 14,85 | 1000   | 32 | M30 | 24  |    | x  | x   | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ----> MFMB 75 M16 x 100