


Product Group JPR

Adjustable feet with hexagonal adjusting screw (swivelling base)




Standard Colours

- black RAL 9005

Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Base 20/25mm: Polyamide (PA)
- Base 30/40mm: Polypropylene (PP)



Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- *) = Production with assembly aid Pozidriv 2 in the base (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

Product options on inquiry

- Further thread lengths/sizes
- Hexagon socket in thread end (please look at JPR ISK)
- Plastic base in special colours according to RAL-System

D	F max.	H	H1	M	WAF	16	20	30	40	50	60	70	80	90	100	120
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
20	400	10	16	M8	13	x	x	x	x	x	x	x	x	x	x	x
20	550	10	16,5	M10	17	x	x	x	x	x	x	x	x	x	x	x
25	400	10	16	M8	13	x	x	x	x	x	x	x	x	x	x	x
25	550	10	16,5	M10	17	x	x	x	x	x	x	x	x	x	x	x
25	650	10	18	M12	19			x	x	x	x	x	x	x	x	x
30	400	10	16	M8	13	x	x	x	x	x	x	x	x	x	x	x
30	550	10	16,5	M10	17	x	x	x	x	x	x	x	x	x	x	x
30	650	10	18	M12	19			x	x	x	x	x	x	x	x	x
40	400	10	15	M8	13	x	x	x	x	x	x	x	x	x	x	x
40	550	10	16,5	M10	17	x	x	x	x	x	x	x	x	x	x	x
40	650	10	18	M12	19			x	x	x	x	x	x	x	x	x

Ordering example

- Group + D + M + Thread Length ---> JPR 40 M10x 50