




Product Group MFSSR

Machine feet made of stainless steel with vulcanized rubber pad



Material

- Base body: AISI 304 (A2)
- Rubber: NBR 80 Shore, vulcanized



Product information

- Depending on the size of the thread or the foot diameter, the machine foot is provided with a chamfer on both sides or with a hexagon as a spanner flat.
- The foot is made of pressed moulded sheet metal. The vulcanized rubber is firmly attached to the sheet. This prevents the penetration of bacteria and ensures a high standard of hygiene.
- Die abgerundete Form und der verdeckte Übergang vom Fuß zum Gewinde erleichtern die Reinigung.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Food industry

Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)

D	F max.	H	H1	M	WAF	50	75	100	125	150	175	200	225	250
mm	kg	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
50	400	19	29	M10	14	x	x	x	x					
50	400	19	29	M12	14	x	x	x	x					
50	400	19	29	M14	14		x	x	x	x				
50	400	19	34	M16	13		x	x	x	x				
80	1000	25	35	M14	14	x	x			x	x			
80	1000	25	35	M10	14		x	x						
80	1000	25	35	M12	14			x	x					
80	1000	25	35	M16	13		x	x	x	x	x			
80	1000	25	38	M20	17		x	x	x	x	x	x	x	
80	1000	25	40	M24	20		x	x	x	x	x	x	x	
100	1500	30	39,5	M16	13		x	x	x	x	x	x		
100	1500	30	43	M20	17		x	x	x	x	x	x	x	x
100	1500	30	44	M24	20			x	x	x	x	x	x	x
100	1500	30	44	M30	26			x	x	x	x	x	x	x
120	3000	32	47	M16	13		x	x	x	x	x			
120	3000	32	47	M20	17		x	x	x	x	x	x	x	x
120	3000	32	47	M24	20			x	x	x	x	x	x	x
120	3000	32	49	M30	26			x	x	x	x	x	x	x



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

Ordering example

• Group + D + M + Thread Length ----> MFSSR 50 M10x 50