



Product Group MFTH

Machine feet made of stainless steel with sealing bush, fixing system and vulcanized rubber pad



Material

- Base body: AISI 304 (A2)
- Rubber: NBR 80 Shore, vulcanized



Product information

- The machine base has a sealing bush that covers parts of the thread. An O-ring is incorporated inside the bush. The sealing ring prevents the penetration of dirt by mechanically sticking to the thread surface. Thus the strictest legal hygiene standards are fulfilled.
- Die abgerundete Form und der verdeckte Übergang vom Fuß zum Gewinde erleichtern die Reinigung.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Character dimension "L2" corresponds to the maximum usable stroke in mm.
- Pharmaceutical industry, food industry, beverage industry, dairies, chemical industry

Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)
- Rubber-pad made of white EPDM (high resistance against chemical degreaser and solvent)

Order Number	B	D	D1	d	F max.	H	H1	L	L1	L2	M	WAF	SW1
	mm	mm	mm	mm	kg	mm	mm	mm	mm	mm		mm	mm
MFTH 80 / M16x125	54	80	25	15	1000	25	38	125	60	40	M16	17	20
MFTH 80 / M16x150	54	80	25	15	1000	25	38	150	60	40	M16	17	20
MFTH 80 / M20x150	54	80	30	15	1000	25	38	150	60	40	M20	17	26
MFTH 100 / M16x150	69	100	25	15	1500	30	43	150	60	40	M16	17	20
MFTH 100 / M20x150	69	100	30	15	1500	30	43	150	60	40	M20	17	26
MFTH 100 / M24x150	69	100	35	15	1500	30	44	150	60	40	M24	20	30
MFTH 100 / M30x150	69	100	42	15	1500	30	44	150	60	40	M30	26	36